

Declaration of Performance

(according to regulation EU No 305/2011)

Unique ID code

No. TSUK ComFlor® 210 load bearing ComFlor® ComFlor® 210, 1.00 & 1.25 mm, S350GD+Z275 (component specification TQ 000-05-210-B)

Harmonised

According to EN 1090-1:2009+A1:2011

standard Intended

Load bearing ComFlor®

use-

Manufacturer

Tata Steel UK Limited Shotton Works, Deeside, Flintshire, CH5 2NH Tel: +44 (0)1244 892199

Website: www.tatasteeleurope.com

Authorised Representative

Mark Denys - Quality Director. Tata Steel Wenckebachstraat 1 . Velsen Noord . 1951 JZ . NL . PO Box 10.000 . IJmuiden 1970 . CA. NL

System of AVCP

System of assessment and verification of constancy of performance of the product System 2+

Notified Body LRQA Verification B.V,George Hintzenweg 77, 3068 AX Rotterdam, The Netherlands. No. 2814 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited

Signed for and on behalf of the manufacturer by:-



Jo Evans - Director, Building System UK Tata Steel UK

Limited

Declared Performance/s

Essential characteristic	Performance	Harmonised technical specification
Tolerances on dimensions and shape	EN 1090-2 clause 11.2.2.3	
Weldability	NPD	
Fracture toughness	NPD	
Reaction to fire	A1	
Release of cadmium and its compounds	NPD	EN 1090-1:2009+A1:2011
Emission of radioactivity	NPD	
Durability	NPD	
Execution class (EXC)	EXC4	
Structural characteristics - Design:	NPD	



 ϵ

2814 / CPR / LRQ00002892

Tata Steel Strip Products UK

2814

TSUK ComFlor® 210 load bearing ComFlor®

EN 1090-1:2009+A1:2011

ComFlor® 210 Load bearing ComFlor®

profile

To be used in - Load bearing ComFlor®

Geometrical data (tolerances in dimensions and shape) EN 1090-2

Weldability NPD

Fracture toughness of structural steel products NPD

Reaction to fire Class A1

Release of cadmium and its compounds NPD

Emission of radioactivity NPD

Durability NPD

Execution class (EXC) EXC 4

Structural characteristics -Design: NPD

Sensitivity: general