



(according to regulation EU No 305/2011) Unique ID code No. TSUK D60 load bearing RoofDek D60, 0.70, 0.90 & 1.20 mm, S220GD, HPS200 Colorcoat Últra (component specification TQ 000-06-60-B) Harmonisod standard Intended According to EN 1090-1:2009+A1:2011 Load bearing RoofDek Tata Steel UK Limited Manufacturer Shotton Works. Deeside, Flintshire, CH5 2NH Tel: +44 (0)1244 892199

Declaration of Performance

Authorised Representative

1100-

Mark Denys - Quality Director. Tata Steel Wenckebachstraat 1. Velsen Noord 1951 JZ NI PO Box 10.000. IJmuiden 1970 . CA. NL

Website : www.tatasteeleurope.com

System of AVCP

System of assessment and verification of constancy of performance of the product System 2+

Notified Body LRQA Verification B.V.George Hintzenweg 77, 3068 AX Rotterdam. The Netherlands. No. 2814 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited

Signed for and on behalf of the manufacturer by:-

Jo Evans - Director, Building System UK Tata Steel UK

Limited

| Essential characteristic | Performance | Harmonised technical specification |
|--|---------------------------|------------------------------------|
| Tolerances on dimensions and shape | EN 1090-2 clause 11.2.2.3 | - |
| Weldability | NPD | |
| Fracture toughness | NPD | |
| Reaction to fire | A1 | |
| Release of cadmium and its compounds | NPD | EN 1090-1:2009+A1:2011 |
| Emission of radioactivity | NPD | |
| Durability | NPD | |
| Execution class (EXC) | EXC4 | |
| Structural characteristics - Design: | NPD | |

Declared Performance/s

CE

2814 / CPR / I RO00002892

Tata Steel Strip Products UK

2814

TSUK D60 load bearing RoofDek

EN 1090-1:2009+A1:2011

D60 Load bearing RoofDek profile

To be used in - Load bearing Roof Deck

| $Geometrical \ data \ ({\rm tolerances} \ {\rm in} \ dimensions \ {\rm and} \ {\rm shape})$ | EN 1090-2 |
|---|---------------|
| Weldability | NPD |
| Fracture toughness of structural steel products | NPD |
| Reaction to fire | Class C s2 d0 |
| Release of cadmium and its compounds | NPD |
| Emission of radioactivity | NPD |
| Durability | NPD |
| Execution class (EXC) | EXC 4 |
| Structural characteristics -Design: | NPD |

Date:- 20/03/2023