

A continuous run of 6mm dia high grade butyl mastic (min 25 yr guarantee)

Parapet flashing max unsupported length 200mm butt or lap jointed and sealed with two runs of continuous 4mm dia high grade butyl mastic (min 25 yr guarantee)

Self drilling self tapping primary fastener with minimum 15mm dia washers

Continuous run of 4mm dia high grade butyl mastic (25 yr warranty)

A continuous run of 6mm dia high grade butyl mastic (min 25 yr guarantee)

Sealed rivets or self drilling fasteners with sealing washers at max 450mm centres

Trisomet® 333 system

Factory made insulated gutter

©Tata Steel UK Limited.

All support steelwork by others

Trimapanel® U-values

Depth 70 = 0.31 W/m²K.
Depth 90 = 0.24 W/m²K.
Depth 120 = 0.17 W/m²K.

Junction 'psi' and 'fi' values

$\Psi =$ W/mK.
 $f =$

Stated calculation results are dependent on components being as shown.
Computer modelled in accordance with EN ISO 10211



Tata Steel retain the right to amend the construction and technical specifications shown on this drawing without prior notice.

TATA STEEL

SALES TEL: 01244 892199
TECHNICAL TEL: 01244 892133/34

www.tatasteelconstruction.com

PROJECT **Trimapanel® System
Typical Details**

TITLE
Parapet

| | | | |
|----------|-----|-------|-----|
| DRAWN BY | JCA | SCALE | NTS |
|----------|-----|-------|-----|

| | | | |
|-------------|----|------------|--|
| APPROVED BY | DA | TOLERANCES | |
|-------------|----|------------|--|

| | | | |
|------|----------|----------|-------------|
| DATE | 22/11/10 | DRG. No. | W2-016-02-B |
|------|----------|----------|-------------|