

Span/load tables

Trisomet, 100 mm core

Jan-15

The span tables below have been created in accordance with EN 14509. For the use of roof cladding only
 The values are based on a maximum permitted deflection of span/200
 Fastener performance has been taken into account within these tables based on a 2mm thick steel purlin/rail and assuming 3 fasteners per support.

The panel is assumed to have a minimal land of 65 mm at each support position

If the perimeters above do not suit the specification of your project please contact our Technical Department who will be happy to adjust these to suit and produce a new set of load span data.

Safe Imposed (positive) Loads (kN/m²)

Span (m)	1.20	1.40	1.60	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20
Single span	6.02	5.35	4.81	4.35	3.95	3.59	3.27	2.96	2.60	2.29	2.03
Double span	4.00	3.15	2.57	2.14	1.82	1.57	1.37	1.21	1.08	0.97	0.87
Multi span	4.39	3.43	2.78	2.31	1.97	1.70	1.49	1.32	1.18	1.06	0.96

Safe Wind Suction (negative) Loads (kN/m²)

Span (m)	1.20	1.40	1.60	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20
Single span	-6.20	-5.53	-4.99	-4.53	-4.13	-3.77	-3.45	-3.15	-2.89	-2.66	-2.45
Double span	-4.07	-3.23	-2.66	-2.24	-1.93	-1.69	-1.50	-1.35	-1.22	-1.12	-1.03
Multi span	-4.45	-3.50	-2.86	-2.40	-2.07	-1.81	-1.61	-1.44	-1.31	-1.20	-1.11

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel Europe Limited, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Building Systems UK

Shotton Works • Deeside • Flintshire • CH5 2NH • UK

T: +44 (0) 1244 892199 • F: +44 (0) 1244 892121 • www.tatasteelconstruction.com/theworks
 Tata Steel UK Limited • 30 Millbank • London SW1P 4WY • Registered in England No. 2280000