

**Declaration of Performance**  
(according to regulation EU No 305/2011)

Unique ID code **No. TSUK ComFlor® 60 load bearing ComFlor®  
ComFlor® 60, 0.90, 1.00 & 1.20 mm, S350GD+Z275  
ComFlor® 60, 0.90, 1.00 & 1.20 mm, S350GD FD25 Colorcoat  
(component specification TQ 000-06-046-A)**

Harmonised standard  
Intended use- **According to EN 1090 Part 1 2009**  
Load bearing ComFlor®

Manufacturer **Tata Steel UK Limited**  
Shotton Works,  
Deeside, Flintshire,  
CH5 2NH  
Tel: +44 (0)1244 892199  
Website : www.tatasteelurope.com

Authorised Representative **David Phillips - Quality Manager.**  
Tata Steel  
Shotton Works,  
Deeside,  
Weighbridge Rd,  
Flintshire CH5 2NH

System of AVCP **System of assessment and verification of constancy of  
performance of the product**  
System 2+

Notified Body Lloyds Register Verification B.V inspection  
Services No. 2814 performed the inspection of the  
manufacturing plant, factory production control, the continuous  
surveillance assessment and evaluation. The performance of  
the product identified above is in conformity with the set of  
declared performance/s. This declaration of performance is  
issued under the sole responsibility of Tata Steel UK limited

Signed for and on behalf of the manufacturer by:-



Jo Evans - Director, Building System UK  
Tata Steel UK Limited

Date:- 28/05/2021

Declared Performance/s

| Essential characteristic             | Performance               | Harmonised technical specification |
|--------------------------------------|---------------------------|------------------------------------|
| Tolerances on dimensions and shape   | EN 1090-2 clause 11.2.2.3 | EN 1090-1:2009+A1:2011             |
| Weldability                          | NPD                       |                                    |
| Fracture toughness                   | NPD                       |                                    |
| Reaction to fire                     | A1                        |                                    |
| Release of cadmium and its compounds | NPD                       |                                    |
| Emission of radioactivity            | NPD                       |                                    |
| Durability                           | NPD                       |                                    |
| Execution class (EXC)                | EXC4                      |                                    |

# UK CA

0038 / CPR / LR00002892

Tata Steel  
Strip Products UK

21

TSUK ComFlor® 60 load bearing ComFlor®

EN 1090-1:2009+A1:2011

ComFlor® 60 Load bearing ComFlor® profile

To be used in - Load bearing ComFlor®

|   |           |
|---|-----------|
| Geometrical data (tolerances in dimensions and shape) | EN 1090-2 |
| Weldability   | NPD       |
| Fracture toughness of structural steel products       | NPD       |
| Reaction to fire                                      | Class A1  |
| Release of cadmium and its compounds                  | NPD       |
| Emission of radioactivity                             | NPD       |
| Durability  | NPD       |
| Execution class (EXC)                                 | EXC 4     |