

## Vetex<sup>®</sup>

### Safety barrier products

Vetex systems are suitable for both high and low speed road applications, where normal containment is required. It is designed to contain average sized vehicles with a mass of 1500kg. This type of barrier is used on motorways, trunk and non-trunk roads, in verges and central reservations. Vetex safety barrier products are fully compliant with the requirements of BS EN 1317.



#### Key features

- Improved post centres
- Standard beam across systems (C501 5 metre beam)
- Standard post option across systems
  - Surface mounted
  - Excavated
  - Socketed
  - Driven
  - Long driven

#### Latest Vetex systems

| System | Application  | Working class width | Post spacing (m) | ASI Rating |
|--------|--------------|---------------------|------------------|------------|
| N1     | Single sided | W2                  | 5.0 metre        | A          |
| N2     | Single sided | W1                  | 2.0 metre        | A          |
| N2     | Single sided | W2                  | 2.5 metre        | A          |
| N2     | Single sided | W3                  | 4.0 metre        | A          |
| N2     | Single sided | W4                  | 5.0 metre        | A          |
| N2     | Single sided | W5                  | 8.0 metre        | A          |
| N2     | Double sided | W2                  | 3.0 metre*       | B          |
| N2     | Double sided | W3                  | 4.5 metre        | B          |
| N2     | Double sided | W4                  | 7.5 metre        | B          |
| N2     | Double sided | W5                  | 8.0 metre        | B          |
| H1     | Single sided | W3                  | 2.0 metre        | A          |

\*Also available as a 3.2 metre centre option using a C401 4 metre beam.

All systems are provided as hot dip galvanised to BS EN ISO 1461 and can provide a service life of 20+ years (dependent upon conditions in accordance with specifications for Highways Works Series 400).

**Tata Steel**  
**Construction Products**

Llanwern Works  
Newport, NP19 4QZ  
United Kingdom  
T: +44 (0) 1633 752191  
E: cep.sales@tatasteelurope.com

English Language DE0417:PDF:EN:0319/1

[www.tatasteelurope.com](http://www.tatasteelurope.com)

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel Europe Limited, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Copyright 2019  
Tata Steel Europe Limited