

Declaration of Performance

(according to Regulation EU No 305/2011)

Ref. TST Hybox355-J2H

Cold formed structural hollow sections produced from steel Grade S355J2H / 1.0576 according to EN 10219-1

For use in structural fabrications in accordance with EN 1090,
when supplied with 3.1 certification to EN 10204 containing
product identification details.

Tata Steel - Tubes Europe
Head Office
PO Box 101, Weldon Road
Corby, NN17 5UA
Tel: +44 (0)1536 402121
Website : www.tatasteleurope.com

System of assessment and verification of constancy of
performance of the product
System 2+

NL - FPC Certificate No: 0038/CPR/RQA20070001/A
UK - FPC Certificate No: 0038/CPR/LRQ0840080/B

Notified factory production control certification body No. 0038
performed the initial inspection of the manufacturing plant and of
factory production control and the continuous surveillance,
assessment, and issued the certificate of conformity of the factory
production control

Notified Body
Lloyds Register Verification Limited
71 Fenchurch Street, London, EC3M 4BS
Tel :+44 (0)207 423 2428
Email : ecdirectives@lr.org
Website : www.lr.org

Essential characteristic	Performance			Harmonised technical specification
	Nominal thickness (mm)		Values min (MPa)	
Yield strength	>	<=	355	EN10219-1 2006
	-	16		
Tensile strength	Nominal thickness (mm)		Values (MPa)	
	>	<=	min max	
	-	3	510 680	
	3	16	470 630	
Elongation	Nominal thickness (mm)		Values min (%)	
	>	<=	long.	
		16	20 (18 where Table A.3 Note c applies)	
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	Impact Value min. average (J) at Test Temp (°C)	
	J2H	<=16	27J at -20°C	
Weldability (CEV)	Nominal thickness (mm)		Values max (%)	
	>	<=	0,45	
Durability	Nominal thickness (mm)		Composition (cast) (max. unless otherwise shown)	
	<=16		C: 0.22 Si: 0.55 Mn: 1.60 P: 0.030 S: 0.030	
			FF deoxidation*	
Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating				
Tolerances on dimensions and shape	Round, square and rectangular hollow sections	In accordance with EN 10219-2: 2006		

Notes: *FF – Fully killed steel containing nitrogen binding elements



0038

Tata Steel
Tubes Europe
PO Box 101, Weldon Road Road
Corby, NN17 5UA, UK

13

Ref. TST Hybox355-J2H

EN 10219-1: 2006

Cold formed structural hollow sections produced from steel Grade S355J2H / 1.0576 according to EN 10219-1

For use in structural fabrications in accordance with EN 1090,
when supplied with 3.1 certification to EN 10204 containing
product identification details.

Information on regulated characteristics in accordance with
EN10219 for:

Elongation :
Tensile Strength :
Yield Strength :
Impact Strength :
Weldability :
Durability :

Dangerous Substances : No Performance Determined

