


Celsius® S460NH

Fully normalized high strength hollow sections

Celsius® S460NH is a range of fully normalized structural hollow sections according to EN 10210 with minimum yield strength 460 MPa. As with all Celsius® hollow sections, S460NH is fully normalized, so is essentially free of internal stresses, with tight corner radii, less than 2T.



The high yield strength of Celsius® S460NH delivers improved load-bearing capabilities in a multitude of applications. In all cases where yield strength is a limiting factor, a lighter-weight section can be used within the standard gauge range, compared to a standard equivalent S355 section. This can save at least 20% of steel weight based on standard gauges.

Celsius® S460NH also benefits from a uniquely low CEV of ≤ 0.45 . Coupled with the lack of any internal stresses, this makes it the most weldable range of high strength hollow sections. The chemistry of steel used is also ideally suited for galvanizing and is highly resistant to fatigue.

Tolerances

Dimensional tolerances are to EN 10210: Part 2 except for corner radius which is max 2T (standard states max 3T).

Inspection & Testing

Celsius® S460NH hollow sections are subject to specific inspection and testing and are supplied with an inspection certificate type 3.1 to EN 10204. All Celsius® sections undergo 100% weld line NDT inspection to either E4 or U5 standard.

Designation

Celsius® S460NH hollow sections are designated by their product name, outside dimensions and thickness in millimetres.

CE Marking

Celsius® S460NH is manufactured and CE marked according to EN 10210-1&2:2006 grade S460NH.

Sustainability

The essential properties of steel make it the sustainable choice for a wide range of applications. Steel is strong, durable, versatile, re-usable and most importantly, it is 100% recyclable. We take sustainability very seriously and have gained a 'very good' rating for responsible sourcing according to BES 6001. Celsius is also available with an Environmental Product Declaration (EPD).



Mechanical properties

Yield strength ReH min N/mm ²	Tensile strength R _m N/mm ²	Elongation % min L ₀ = 5,65 √S ₀ specimen	Impact strength 10mm x 10mm		Carbon equivalent (CEV) max
T ≤ 16mm	3mm < T ≤ 100mm	T	°C	J	
460	540-720	17	-40	27	0.45

Chemical composition % by mass

C max	Si max	Mn	P max	S max	Nb max	V max	Al total min	Ti max	Cr max	Ni max	Mo max	Cu max	N max
0.22	0.60	1.70	0.035	0.030	0.050	0.20	0.020	0.03	0.30	0.80	0.10	0.70	0.025

Note: CEV ≤ 0.45

Availability

Celsius® S460NH is available across the size range indicated in the tables. Intermediate sizes may be available – please ask.

Minimum order quantities may apply – please contact your Tata Steel representative for details.

Celsius® S460NH is available with internal weld bead trimmed where specified.

Celsius® S460NH is available in standard lengths from 6.0m to 14.5m for sizes up to 100/100 or 120/80 and up to 15.3m for all other sizes.

Technical Support

We want you to get the best from Celsius® hollow sections. Our technical engineers and trained sales staff are always happy to answer your questions on steel selection and application. Our engineers are available to assist you with the application of Celsius® S460NH, including it's use in construction and in light-weighting of machinery. We can also provide leading advice on welded joints, including software which can help in their design.

Rectangular hollow sections (RHS)

mm	3.2	3.6	4.0	5.0	6.3	8.0	10.0	12.5	16.0
50/30	■	■	■	■					
60/40	■	■	■	■					
80/40	■	■	■	■					
90/50	■	■	■	■					
100/50	■	■	■	■					
100/60	■	■	■	■					
120/60		■	■	■					
120/80		■	■	■					
200/120				■	■	■	■	■	■
200/150				■	■	■	■	■	■
250/100				■	■	■	■	■	■
250/150				■	■	■	■	■	■
300/100				■	■	■	■	■	■
300/200				■	■	■	■	■	■
350/150				■	■	■	■	■	■
350/250					■	■	■	■	■
400/200					■	■	■	■	■
400/300						■	■	■	■
450/250						■	■	■	■
500/200						■	■	■	■
500/300						■	■	■	■

Square hollow sections (SHS)

mm	3.2	3.6	4.0	5.0	6.3	8.0	10.0	12.5	16.0
40/40	■	■	■	■					
50/50	■	■	■	■					
60/60	■	■	■	■					
70/70	■	■	■	■					
80/80	■	■	■	■					
90/90		■	■	■					
100/100		■	■	■					
160/160				■	■	■	■	■	■
180/180				■	■	■	■	■	■
200/200				■	■	■	■	■	■
250/250				■	■	■	■	■	■
300/300				■	■	■	■	■	■
350/350					■	■	■	■	■
400/400						■	■	■	■

www.tatasteelconstruction.com

Tata Steel

Weldon Road
Corby, Northants, NN17 5UA
United Kingdom
T: +44 (0) 1536 404261
E: tubes@tatasteel.com
www.tatasteelconstruction.com/celsius

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Before using products or services supplied or manufactured by Tata Steel and its subsidiaries, customers should satisfy themselves as to their suitability.

Copyright 2020
Tata Steel Europe Limited